

**Description**

Fastener Length: 1-23/64", Thread: 3/8-24, Thread Length: 25/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS656V12
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-915-4951
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS656V12 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.391 Inches Nominal
<b>Fastener Length:</b>	1.314 Inches Minimum And 1.359 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.188 Inches Minimum And 0.203 Inches Maximum
<b>Width Between Flats:</b>	0.553 Inches Minimum And 0.564 Inches Maximum
<b>Grip Diameter:</b>	0.374 Inches Minimum And 0.375 Inches Maximum
<b>Point Diameter:</b>	0.374 Inches Nominal
<b>Shank Unthreaded Hole Diameter:</b>	0.106 Inches Minimum Overall And 0.116 Inches Maximum Overall
<b>Point Style:</b>	Flat
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Grip Length:</b>	0.745 Inches Minimum And 0.765 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Material:</b>	Titanium Alloy Uns R54520 Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS656V12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.