

**Description**

Fastener Length: 7-61/64", Thread: 3/8-24, Thread Length: 13/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS656V121D
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-326-4759
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE  
AVAILABLE

## P/N NAS656V121D Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.366 Inches Minimum And 0.416 Inches Maximum
<b>Fastener Length:</b>	7.938 Inches Minimum And 7.968 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.188 Inches Minimum And 0.203 Inches Maximum
<b>Width Between Flats:</b>	0.553 Inches Minimum And 0.564 Inches Maximum
<b>Grip Diameter:</b>	0.3740 Inches Minimum And 0.3745 Inches Maximum
<b>Shank Unthreaded Hole Diameter:</b>	0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Grip Length:</b>	7.552 Inches Minimum And 7.572 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	7.810 Inches Minimum First Hole And 7.860 Inches Maximum First Hole
<b>Surface Finish:</b>	16.0 Microinches Threads
<b>Surface Finish:</b>	63.0 Microinches Bearing Surface Of Head
<b>Surface Finish:</b>	63.0 Microinches Grip
<b>Material:</b>	Titanium Alloy Overall
<b>Material Document And Classification:</b>	Nas 621 Assn Std Single Material Response Overall Or Ams 4928 Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas656 Professional/industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS656V121D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.