

Description

Fastener Length: 1-11/32", Thread: 3/8-24, Thread Length: 13/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS656V15D
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-253-3707
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE
AVAILABLE

P/N NAS656V15D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.366 Inches Minimum And 0.416 Inches Maximum
Fastener Length:	1.314 Inches Minimum And 1.344 Inches Maximum
Head Style:	Hexagon
Head Height:	0.188 Inches Minimum And 0.203 Inches Maximum
Width Between Flats:	0.553 Inches Minimum And 0.564 Inches Maximum
Grip Diameter:	0.3740 Inches Minimum And 0.3745 Inches Maximum
Shank Unthreaded Hole Diameter:	0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.928 Inches Minimum And 0.948 Inches Maximum
Thread Quantity Per Inch:	24
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.186 Inches Minimum First Hole And 1.236 Inches Maximum First Hole
Surface Finish:	16.0 Microinches Threads
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Surface Finish:	63.0 Microinches Grip
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas656 Professional/industrial Association Standard

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS656V15D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.