

**Description**

Fastener Length: 5-1/64", Thread: 7/16-20, Thread Length: 7/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS657V73D                                |
| Minimum Qty (MOQ):      | 1 EA                                      |
| NSN:                    | 5306-01-478-7765                          |
| Schedule B:             | 8108.90.3060                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

# P/N NAS657V73D Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 3a  |
| <b>Thread Direction:</b>  | Right-hand  |
| <b>Thread Length:</b>   | 0.453 Inches Nominal  |
| <b>Fastener Length:</b>   | 5.000 Inches Minimum And 5.030 Inches Maximum                           |
| <b>Head Style:</b>  | Hexagon   |
| <b>Head Height:</b>   | 0.219 Inches Minimum And 0.234 Inches Maximum                           |
| <b>Width Between Flats:</b>   | 0.679 Inches Minimum And 0.690 Inches Maximum                           |
| <b>Grip Diameter:</b>   | 0.4365 Inches Minimum And 0.4370 Inches Maximum                         |
| <b>Shank Unthreaded Hole Diameter:</b>                                  | 0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole     |
| <b>End Item Identification:</b>   | F18 E/f   |
| <b>Nominal Thread Diameter:</b>   | 0.4375 Inches   |
| <b>Grip Length:</b>   | 4.552 Inches Minimum And 4.572 Inches Maximum                           |
| <b>Thread Quantity Per Inch:</b>  | 20  |
| <b>Minimum Tensile Strength:</b>  | 160000 Pounds Per Square Inch   |
| <b>Criticality Code Justification:</b>                                  | Agav  |
| <b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b> | 4.885 Inches Minimum First Hole And 4.895 Inches Maximum First Hole     |
| <b>Part Name Assigned By Controlling Agency:</b>                        | Bolt,close Tolerance - Hexagonhead,titanium, Short Thread, .190 To .500 |
| <b>Material:</b>  | Titanium Alloy Overall  |
| <b>Material Document And Classification:</b>                            | Ams4967 Comp 6al-4v Assn Std Single Material Response Overall           |
| <b>Thread Series Designator:</b>  | Unf   |
| <b>Specification/standard Data:</b>                                     | 80205-nas657 Professional/industrial Association Standard               |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS657V73D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.