

**Description**

Fastener Length: 63/64", Thread: 10-32, Thread Length: 23/64", NAS6603 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                           |
|-------------------------|-------------------------------------------|
| SKU / Model:            | NAS660310X                                |
| Minimum Qty (MOQ):      | 25                                        |
| NSN:                    | 5306-01-255-4605                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N NAS6603-10X Specifications

|                                                       |                                                                                                                                                           |
|-------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Thread Class:</b>                                  | 3a                                                                                                                                                        |
| <b>Thread Direction:</b>                              | Right-hand                                                                                                                                                |
| <b>Thread Length:</b>                                 | 0.320 Inches Minimum And 0.370 Inches Maximum                                                                                                             |
| <b>Fastener Length:</b>                               | 0.955 Inches Minimum And 0.985 Inches Maximum                                                                                                             |
| <b>Head Style:</b>                                    | Dished Hexagon                                                                                                                                            |
| <b>Head Height:</b>                                   | 0.110 Inches Minimum And 0.125 Inches Maximum                                                                                                             |
| <b>Width Between Flats:</b>                           | 0.367 Inches Minimum And 0.376 Inches Maximum                                                                                                             |
| <b>Shoulder Diameter:</b>                             | 0.2016 Inches Minimum First Shoulder And 0.2026 Inches Maximum First Shoulder                                                                             |
| <b>Shoulder Length:</b>                               | 0.615 Inches Minimum First Shoulder And 0.635 Inches Maximum First Shoulder                                                                               |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches                                                                                                                                              |
| <b>Thread Quantity Per Inch:</b>                      | 32                                                                                                                                                        |
| <b>Shoulder Shape:</b>                                | Round First Shoulder                                                                                                                                      |
| <b>Material:</b>                                      | Steel Comp E4340 Overall Or Steel Comp 8740 Overall                                                                                                       |
| <b>Material Document And Classification:</b>          | Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall                                                                                                                      |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall                                                                                             |
| <b>Thread Series Designator:</b>                      | Unjf                                                                                                                                                      |
| <b>Specification/standard Data:</b>                   | 80205-nas6603 Professional/industrial Association Standard                                                                                                |

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6603-10X> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.