

## **P/N NAS6603-25**

## **Description**

Fastener Length: 1-29/32", Thread: 10-32, Thread Length: 11/32", NAS6603 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS660325

Minimum Qty (MOQ): 25

NSN: 5306-01-482-2247

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# **P/N NAS6603-25 Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.345 Inches Nominal
Fastener Length:	1.907 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Grip Diameter:	0.188 Inches Minimum And 0.189 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	1.562 Inches Nominal
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Ams6415 Assn Std 2nd Material Response Overall Or Mil-s-5000 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Tyii, Cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

### **How to Order**

Order this shear bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6603-25">https://military-fasteners.com/bolts/shear+bolts/NAS6603-25</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.