

P/N NAS6603-26

Military-Fasteners.com

Description

length: 1.97", grip: 1.625", thread: 10-32, hex head, tension, long thread, cadmium plated alloy steel, NAS6603 series bolt

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

| SKU / Model: | NAS660326 |
|-------------------------|---|
| Minimum Qty (MOQ): | 10 |
| NSN: | 5306-01-209-4087 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N NAS6603-26 Specifications

| Thread Direction:Right-handThread Length:0.340 Inches Minimum And 0.350 Inches MaximumFastenr Length:0.350 Inches Minimum And 0.350 Inches MaximumHead Style:Dished HexagonHead Height:0.110 Inches Minimum And 0.125 Inches MaximumWidth Between Flats:0.367 Inches Minimum And 0.376 Inches MaximumHole Diameter:0.464 Inches Minimum And 0.056 Inches MaximumOntill Inches Minimum And 0.056 Inches MaximumHole Diameter:0.1895 Inches Minimum And 0.056 Inches MaximumOminal Thread Diameter:0.190 InchesOntopiameter:0.190 InchesOntopiameter:0.190 InchesOrip Length:1.615 Inches Minimum And 1.635 Inches MaximumHole Quantity:3Hole Quantity Per Inch:3Stel Configuration Style:Bio000 Pounds Per Square InchHole Configuration Style:No Drills In HeadMaterial Decument And Classification:No Drills In HeadMaterial Response Overall Or Stel Comp 8740 OverallAuterial Response Overall Or Ams 6322 Assn StdSurface Treatment Document AndCadminur OverallClassification:Q-p-416.ty 2.t 2 Fed Spec Single Treatment Response OverallClassification:UnifFread Strein Designator:UnifSpecial Freatment Document AndCadminur OverallClassification:Q-p-416.ty 2.t 2 Fed Spec Single Treatment Response OverallClassification:UnifSpecial Freatment Document AndOuterClassification:Unif | Thread Class: | 3a |
|---|---------------------------------------|---|
| Thread Length:0.340 Inches Minimum And 0.350 Inches MaximumFastener Length:1.955 Inches Minimum And 1.965 Inches MaximumHead Style:Dished HexagonHead Height:0.110 Inches Minimum And 0.25 Inches MaximumWidth Between Flats:0.367 Inches Minimum And 0.376 Inches MaximumHole Dlameter:0.046 Inches Minimum And 0.376 Inches MaximumGrip Dameter:0.190 Inches Minimum And 0.1895 Inches MaximumNominal Thread Dlameter:0.190 Inches Minimum And 0.1895 Inches MaximumGrip Length:1.615 Inches Minimum And 0.1895 Inches MaximumHole Quantity:3Hole Type:0.100 Inches Minimum And 0.1895 Inches MaximumHole Type:0.100 Inches Minimum And 0.1895 Inches MaximumHole Quantity:3Hole Guantity:1.615 Inches Minimum And 0.1895 Inches Maximum OverallHole Configuration Style:6.000 Pounds Per Square InchHardenes Rating:0.600 Pounds Per Square InchHole Configuration Style:Hexagon CornersSpecial Features:No Drills In HeadMaterial Bocument And Classification:Scele Comp JavO everall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Amaterial Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Amaterial Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Amaterial Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6049 | | |
| Pastener Length:1.955 Inches Minimum And 1.985 Inches MaximumHead Style:Dished HexagonHead Height:0.110 Inches Minimum And 0.125 Inches MaximumWidth Between Flats:0.367 Inches Minimum And 0.376 Inches MaximumHole Diameter:0.046 Inches Minimum And 0.056 Inches MaximumGrip Diameter:0.1885 Inches Minimum And 0.1895 Inches MaximumNominal Thread Diameter:0.190 InchesGrip Length:1.615 Inches Minimum And 0.1895 Inches MaximumHole Quantity:3Hole Quantity:3Hole Quantity:3Intread Quantity Per Inch:3Stoney Composition Style:1.6000 Pounds Per Square InchHole Configuration Style:1.6000 Pounds Per Square InchHole Configuration Style:No Inills In HeadHoteratition Style:No Inills In HeadMaterial:Ceomp 4340 Overall Or Stell Comp 8740 OverallMaterial:Ceomp 4340 Overall Or Stell Comp 8740 OverallMaterial:Ceomp 4340 Overall Or Stell Comp 8740 OverallStraft Teratment:Quantity Iseps Stell Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response OverallMaterial Response OverallAnd Material Response OverallStraft Teratment:Grim OverallStraft Teratment:Grim OverallMaterial Response OverallAnd Aterial Response OverallStraft Teratment:Grim OverallStraft Teratment:Grim OverallStraft Teratment:Grim OverallStraft Teratment:Grim OverallStraft Teratment:Grim Over | | |
| Head Style:Dished HexagonHead Height:0.110 Inches Minimum And 0.125 Inches MaximumWidth Between Flats:0.367 Inches Minimum And 0.376 Inches MaximumHole Diameter:0.046 Inches Minimum And 0.056 Inches MaximumGrip Diameter:0.1885 Inches Minimum And 0.1895 Inches MaximumNominal Thread Diameter:0.1895 Inches Minimum And 0.1895 Inches MaximumGrip Length:0.161 Inches Minimum And 1.635 Inches MaximumHole Quantity:0.161 Inches Minimum And 1.635 Inches MaximumHole Quantity:0.101 InchesHole Quantity:0.180 Inches Maximum And 0.050 Inches MaximumHole Quantity:0.180 Inches Minimum And 1.635 Inches MaximumHole Quantity:0.101 Inches Minimum And 1.635 Inches MaximumHole Cong Strength:0.101 Inches Maximum And 0.050 Inches MaximumHole Configuration Style:0.1000 Pounds Per Square InchHardness Ratling:0.60 Rockwell C Minimum Overall And 0.0 Rockwell C Maximum OverallHole Configuration Style:No Drills In HeadMaterial Resone Overall Or Steel Comp 8740 OverallMaterial Resone Overall Or Steel Comp 8740 OverallMaterial Resones Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response OverallSurface Treatment Document AndQu-914ty.2t.2t Ped Spec Single Treatment Response OverallThread Steries Designator:Unjf | | |
| Head Height:0.110 Inches Minimum And 0.125 Inches MaximumWidth Between Flats:0.367 Inches Minimum And 0.376 Inches MaximumHole Diameter:0.046 Inches Minimum And 0.056 Inches MaximumGrip Diameter:0.1885 Inches Minimum And 0.1895 Inches MaximumNominal Thread Diameter:0.190 InchesGrip Length:1.615 Inches Minimum And 1.635 Inches MaximumHole Quantity:3Hole Quantity:0.110 Inches Minimum And 0.1895 Inches MaximumHole Type:DrilledThread Olameter:0.000 Pounds Per Square InchHardenss Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallHole Configuration Style:Head (ConrersSpecial Features:No Drills In HeadMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response OverallSurface Treatment:Cadmiun OverallSurface Treatment Document AndQrp-416.ty 2,cl 2 Fed Spec Single Treatment Response OverallThread Series Designator:Unif | - | |
| Width Between Flats:0.367 Inches Minimum And 0.376 Inches MaximumHole Diameter:0.046 Inches Minimum And 0.056 Inches MaximumGrip Diameter:0.1885 Inches Minimum And 0.1895 Inches MaximumNominal Thread Diameter:0.190 InchesGrip Length:1.615 Inches Minimum And 1.635 Inches MaximumHole Quantity:3Hole Type:DrilledThread Quantity Plach:316000 Pounds Per Square InchHole Configuration Style:6.0000 Pounds Per Square InchHole Configuration Style:8.0.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallHoterati5.0.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallHoteration:8.0.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallHoteration:Steel Comp 4340 Overall Or Steel Comp 8740 OverallMaterial:Steel Comp 4340 Overall Or Steel Comp 8740 OverallSurface Treatment:Gadmium OverallSurface Treatment:Gadmium OverallSurface Treatment:Gadmium OverallCassification:Q-p-416,ty 2,cl 2 Fed Spec Single Treatment Response OverallThread Series Designator:Unjf | - | |
| Hole Diameter:0.046 Inches Minimum And 0.056 Inches MaximumGrip Diameter:0.1885 Inches Minimum And 0.1895 Inches MaximumNominal Thread Diameter:0.190 InchesGrip Length:1.615 Inches Minimum And 1.635 Inches MaximumHole Quantity:3Hole Quantity:0.190 InchesThread Quantity:0.190 InchesMinimum Tensile Strength:0.1000 Pounds Per Square InchHole Configuration Style:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallHole Configuration Style:No Drills In HeadMaterial:Steel Comp 4340 Overall Or Steel Comp 8740 OverallSurface Treatment:Camium OverallSurface Treatment:Camium OverallSurface Treatment:Camium OverallCand Streig Document AndQap-416,ty.c.l 2 Fed Spec Single Treatment Response OverallThread Streig Document AndDirils-1000 Ker Single Treatment Response OverallSurface Treatment:Dirils Dirils Dirils In HadeSurface Treatment:Dirils Dirils Dirils In Haterial Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn StdSurface Treatment:Dirils Dirils D | | |
| Grip Diameter:0.1885 Inches Minimum And 0.1895 Inches MaximumNominal Thread Diameter:0.190 InchesGrip Length:1.615 Inches Minimum And 1.635 Inches MaximumHole Quantity:3Hole Type:DrilledDrinled32Minimum Tensile Strength:160000 Pounds Per Square InchHole Configuration Style:Beckgen CornersSpecial Features:No Drills In HeadMaterial:Steel Comp 4340 Overall Or Steer Square InchMaterial:Steel Comp 4340 Overall Or Steer Square InchMaterial:Cadmium Querall And 40.0 Rockwell C Maximum OverallMaterial:Steel Comp 4340 Overall Or Steer Square InchMaterial:Steel Comp 4340 Overall Or Steer Square InchMaterial:Cadmium Querall And 40.0 Rockwell C Maximum OverallMaterial:Steel Comp 4340 Overall Or Steel Comp 8740 OverallSurface Treatment:Cadmium OverallSurface Treatment Document And Classification:Mil-s-Soural Spec Single Treatment Response OverallThread Series Designator:Unjf | Width Between Flats: | 0.367 Inches Minimum And 0.376 Inches Maximum |
| Nominal Thread Diameter:0.190 InchesGrip Length:1.615 Inches Minimum And 1.635 Inches MaximumHole Quantity:3Hole Type:DrilledThread Quantity Per Inch:32Minimum Tensile Strength:16000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon CornersSpecial Features:No Drills In HeadMaterial:Stel Comp 4340 Overall Or Stel Comp 8740 OverallMile-Stongen CornersMile-Stongen CornersSpecial Features:No Mile Special Response Overall Or Mile-Sch49 Mil Special Response Overall Or Mile-Sch49 Mile Special Response OverallSurface Treatment:Cadmium OverallCurrface Treatment Document And Classification:q-p-416.ty 2.cl 2 Fed Spec Single Treatment Response OverallThread Series Designator:Unjf | Hole Diameter: | 0.046 Inches Minimum And 0.056 Inches Maximum |
| Grip Length:1.615 Inches Minimum And 1.635 Inches MaximumHole Quantity:3Hole Type:DrilledThread Quantity Per Inch:32Minimum Tensile Strength:16000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon CornersSpecial Features:No Drills In HeadMaterial:Stel Comp 4340 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response OverallSurface Treatment:Cadmium OverallKurface Treatment Document And Classification:Mil-s-1000 Mil Spec Single Treatment Response OverallThread Series Designator:Unjf | Grip Diameter: | 0.1885 Inches Minimum And 0.1895 Inches Maximum |
| No Quantity:3Hole Type:DrilledThread Quantity Per Inch:32Minimum Tensile Strength:16000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon CornersSpecial Features:No Drills In HeadMaterial:Stel Comp 4340 Overall Or Stel Comp 8740 OverallMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment Document And Classification:orp-416,ty 2,cl 2 Fed Spec Single Treatment Response OverallThread Series Designator:Unif | Nominal Thread Diameter: | 0.190 Inches |
| Hole Type:DrilledThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon CornersSpecial Features:No Drills In HeadMaterial:Steel Comp 4340 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment Document And Classification:Qu-p-416,ty 2,cl 2 Fed Spec Single Treatment Response OverallThread Series Designator:Unjf | Grip Length: | 1.615 Inches Minimum And 1.635 Inches Maximum |
| Thread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon CornersSpecial Features:No Drills In HeadMaterial:Steel Comp 4340 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment Document And Classification:Q-p-416,ty 2,cl 2 Fed Spec Single Treatment Response OverallThread Series Designator:Unjf | Hole Quantity: | 3 |
| Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon CornersSpecial Features:No Drills In HeadMaterial:Steel Comp 4340 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment Document And Classification:Q-p-416,ty 2,cl 2 Fed Spec Single Treatment Response OverallThread Series Designator:Unjf | Hole Type: | Drilled |
| Hardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon CornersSpecial Features:No Drills In HeadMaterial:Steel Comp 4340 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment Document AndQa-p-416,ty 2,cl 2 Fed Spec Single Treatment Response OverallThread Series Designator:Unjf | Thread Quantity Per Inch: | 32 |
| Hole Configuration Style:Hexagon CornersHole Configuration Style:No Drills In HeadSpecial Features:No Drills In HeadMaterial:Steel Comp 4340 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response OverallThread Series Designator:Unjf | Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Special Features:No Drills In HeadMaterial:Steel Comp 4340 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response OverallThread Series Designator:Unjf | Hardness Rating: | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| Material:Steel Comp 4340 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response OverallSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response OverallThread Series Designator:Unif | Hole Configuration Style: | Hexagon Corners |
| Material Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response OverallThread Series Designator:Unif | Special Features: | No Drills In Head |
| Material Document And Classification:2nd Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response OverallThread Series Designator:Unjf | Material: | Steel Comp 4340 Overall Or Steel Comp 8740 Overall |
| Surface Treatment Document And Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall Classification: Unjf | Material Document And Classification: | |
| Classification: Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf | Surface Treatment: | Cadmium Overall |
| | | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall |
| Specification/standard Data: 80205-nas6603 Professional/industrial Association Standard | Thread Series Designator: | Unjf |
| | Specification/standard Data: | 80205-nas6603 Professional/industrial Association Standard |

How to Order

Order this shear bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/shear+bolts/NAS6603-26</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.