

P/N NAS6603-64

Description

Fastener Length: 4-23/64", Thread: 10-32, Thread Length: 11/32",

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

National Motor Freight:

SKU / Model:	NAS660364
Minimum Qty (MOQ):	5
NSN:	5306-01-546-8553
Schedule B:	7318.15.8085
ECCN:	EAR99







095190, Hardware, Noi



^{*} See page 2 for technical characteristics

P/N NAS6603-64 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.345 Inches Nominal
Fastener Length:	4.330 Inches Minimum And 4.360 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Grip Diameter:	0.188 Inches Minimum And 0.189 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	3.990 Inches Minimum And 4.010 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6603-64 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.