

**Description**

Fastener Length: 4-23/64", Thread: 10-32, Thread Length: 11/32",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                       |
|-------------------------|-----------------------|
| SKU / Model:            | NAS660364             |
| Minimum Qty (MOQ):      | 5                     |
| NSN:                    | 5306-01-546-8553      |
| Schedule B:             | 7318.15.8085          |
| ECCN:                   | EAR99                 |
| National Motor Freight: | 095190, Hardware, Noi |



\* See page 2 for technical characteristics

## P/N NAS6603-64 Specifications

|                                  |                                                     |
|----------------------------------|-----------------------------------------------------|
| <b>Thread Class:</b>             | 3a                                                  |
| <b>Thread Direction:</b>         | Right-hand                                          |
| <b>Thread Length:</b>            | 0.345 Inches Nominal                                |
| <b>Fastener Length:</b>          | 4.330 Inches Minimum And 4.360 Inches Maximum       |
| <b>Head Style:</b>               | Dished Hexagon                                      |
| <b>Head Height:</b>              | 0.110 Inches Minimum And 0.125 Inches Maximum       |
| <b>Width Between Flats:</b>      | 0.367 Inches Minimum And 0.376 Inches Maximum       |
| <b>Grip Diameter:</b>            | 0.188 Inches Minimum And 0.189 Inches Maximum       |
| <b>Nominal Thread Diameter:</b>  | 0.190 Inches                                        |
| <b>Grip Length:</b>              | 3.990 Inches Minimum And 4.010 Inches Maximum       |
| <b>Thread Quantity Per Inch:</b> | 32                                                  |
| <b>Minimum Tensile Strength:</b> | 160000 Pounds Per Square Inch                       |
| <b>Material:</b>                 | Steel Comp E4340 Overall Or Steel Comp 8740 Overall |
| <b>Surface Treatment:</b>        | Cadmium Overall And Chromate Overall                |
| <b>Thread Series Designator:</b> | Unjf                                                |

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6603-64> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.