

P/N NAS6603-84

Description

Fastener Length: 5-39/64", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS660384
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-255-4615
Schedule B:	7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS6603-84 Specifications

3a
Right-hand
0.320 Inches Minimum And 0.370 Inches Maximum
5.580 Inches Minimum And 5.610 Inches Maximum
Dished Hexagon
0.110 Inches Minimum And 0.125 Inches Maximum
0.367 Inches Minimum And 0.376 Inches Maximum
0.1885 Inches Minimum And 0.1895 Inches Maximum
0.190 Inches
5.240 Inches Minimum And 5.260 Inches Maximum
32
160000 Pounds Per Square Inch
36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
32.0 Microinches Bearing Surface Of Head
32.0 Microinches Grip
32.0 Microinches Threads
Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Unjf
80205-nas6603 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6603-84 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6603-84 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6603-84 and selecting the quantity you want then click "add to cart".