

P/N NAS6603-9X

Description

Fastener Length: 15/16", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS66039X
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-227-7698
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS6603-9X Specifications

3a
Right-hand
0.320 Inches Minimum And 0.370 Inches Maximum
0.872 Inches Minimum And 0.942 Inches Maximum
Dished Hexagon
0.110 Inches Minimum And 0.125 Inches Maximum
0.367 Inches Minimum And 0.376 Inches Maximum
0.2016 Inches Minimum And 0.2026 Inches Maximum First Shoulder
0.552 Inches Minimum And 0.572 Inches Maximum First Shoulder
0.190 Inches
32
160000 Pounds Per Square Inch
36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum Overall
Round First Shoulder
Steel Comp E4340 Or Steel Comp 8740 Overall
Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Ams6322 Assn Std 2nd Material Response Overall
Cadmium And Chromate Overall
Qq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response Overall
Unjf
80205-nas6603 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6603-9X and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6603-9X and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6603-9X and selecting the quantity you want then click "add to cart".