

**Description**

Fastener Length: 15/16", Thread: 10-32, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS66039X                                 |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5306-01-227-7698                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS6603-9X Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.320 Inches Minimum And 0.370 Inches Maximum  |
| <b>Fastener Length:</b>                               | 0.872 Inches Minimum And 0.942 Inches Maximum  |
| <b>Head Style:</b>                                    | Dished Hexagon   |
| <b>Head Height:</b>                                   | 0.110 Inches Minimum And 0.125 Inches Maximum  |
| <b>Width Between Flats:</b>                           | 0.367 Inches Minimum And 0.376 Inches Maximum  |
| <b>Shoulder Diameter:</b>                             | 0.2016 Inches Minimum And 0.2026 Inches Maximum First Shoulder   |
| <b>Shoulder Length:</b>                               | 0.552 Inches Minimum And 0.572 Inches Maximum First Shoulder   |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches   |
| <b>Thread Quantity Per Inch:</b>                      | 32   |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch  |
| <b>Hardness Rating:</b>                               | 36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum Overall  |
| <b>Shoulder Shape:</b>                                | Round First Shoulder   |
| <b>Material:</b>                                      | Steel Comp E4340 Or Steel Comp 8740 Overall  |
| <b>Material Document And Classification:</b>          | Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Ams6322 Assn Std 2nd Material Response Overall |
| <b>Surface Treatment:</b>                             | Cadmium And Chromate Overall   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response Overall   |
| <b>Thread Series Designator:</b>                      | Unjf   |
| <b>Specification/standard Data:</b>                   | 80205-nas6603 Professional/industrial Association Standard   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6603-9X> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.