

### Description

length: 1.283", grip: 0.938", thread: 10-32, hex head, drilled shank, tension, long thread, cadmium plated alloy steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

### Additional Information

SKU / Model:	NAS6603D15
Minimum Qty (MOQ):	10
NSN:	5306-01-576-0033
ECCN:	EAR99



## P/N NAS6603D15 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.345 Inches Nominal
<b>Fastener Length:</b>	1.377 Inches Minimum And 1.407 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.110 Inches Minimum And 0.140 Inches Maximum
<b>Width Between Flats:</b>	0.367 Inches Minimum And 0.376 Inches Maximum
<b>Grip Diameter:</b>	0.188 Inches Minimum And 0.189 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.922 Inches Minimum And 0.952 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Part Name Assigned By Controlling Agency:</b>	Bolt, Tension, Hex Head, Close Tolerance, Alloy Steel, Long Thread, Reduced Major Diameter, Non-locking, 160 Ksi FtU
<b>Special Features:</b>	Has Drilled Shank
<b>Material:</b>	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Ams6349 Assn Std Single Material Response Overall Or Ams6382 Assn Std Single Material Response Overall Or Ams6415 Assn Std Single Material Response Overall Or Ams6484 Assn Std Single Material Response Overall Or Ams6322 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Ams-qq-p-416, Type II, Class 2 Assn Std Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6603D15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.