

P/N NAS6603DH2

Military-Fasteners.com

Description

Fastener Length: 31/64", Hole Diameter: 3/64", Thread: 10-32, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

SKU / Model:	NAS6603DH2
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-560-7603
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS6603DH2 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.345 Inches Nominal
Fastener Length:	0.455 Inches Minimum And 0.485 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Hole Diameter:	0.046 Inches Minimum And 0.056 Inches Maximum
Grip Diameter:	0.115 Inches Minimum And 0.135 Inches Maximum
Shank Unthreaded Hole Diameter:	0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.052 Inches Minimum And 0.072 Inches Maximum
Hole Quantity:	3
Hole Type:	Drilled
Thread Quantity Per Inch:	32
Hole Configuration Style:	Hexagon Corners
Distance From Head Largest Bearing Surface To Shank Hole Center:	0.306 Inches Nominal First Hole
lii Part Name Assigned By Controlling Agency:	Navy Special Project
Material:	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec Single Material Response Overall Or Ams 6415 Assn Std Single Material Response Overall Or Mil-s-5000 Mil Spec Single Material Response Overall Or Mil-s-6049 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Type li. Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/shear+bolts/NAS6603DH2</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.