

**Description**

Fastener Length: 39/64", Hole Diameter: 3/64", Thread: 10-32, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS6603DH4                                |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5306-01-198-2445                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

# P/N NAS6603DH4 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>  | 3a   |
| <b>Thread Direction:</b>  | Right-hand   |
| <b>Thread Length:</b>   | 0.320 Inches Minimum And 0.370 Inches Maximum  |
| <b>Fastener Length:</b>   | 0.580 Inches Minimum And 0.610 Inches Maximum  |
| <b>Head Style:</b>  | Hexagon  |
| <b>Head Height:</b>   | 0.110 Inches Minimum And 0.125 Inches Maximum  |
| <b>Width Between Flats:</b>   | 0.367 Inches Minimum And 0.376 Inches Maximum  |
| <b>Hole Diameter:</b>   | 0.046 Inches Minimum And 0.056 Inches Maximum  |
| <b>Grip Diameter:</b>   | 0.1885 Inches Minimum And 0.1895 Inches Maximum  |
| <b>Shank Unthreaded Hole Diameter:</b>                                  | 0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole  |
| <b>Nominal Thread Diameter:</b>   | 0.190 Inches   |
| <b>Grip Length:</b>   | 0.240 Inches Minimum And 0.260 Inches Maximum  |
| <b>Hole Quantity:</b>   | 3  |
| <b>Hole Type:</b>   | Drilled  |
| <b>Thread Quantity Per Inch:</b>  | 32   |
| <b>Minimum Tensile Strength:</b>  | 160000 Pounds Per Square Inch  |
| <b>Hole Configuration Style:</b>  | Hexagon Flats  |
| <b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b> | 0.406 Inches Minimum First Hole And 0.456 Inches Maximum First Hole  |
| <b>Surface Finish:</b>  | 32.0 Microinches Bearing Surface Of Head   |
| <b>Surface Finish:</b>  | 32.0 Microinches Grip  |
| <b>Surface Finish:</b>  | 32.0 Microinches Threads   |
| <b>Material:</b>  | Steel Comp E4340 Overall Or Steel Comp 8740 Overall  |
| <b>Material Document And Classification:</b>                            | Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall |
| <b>Surface Treatment:</b>   | Cadmium Overall And Chromate Overall   |
| <b>Surface Treatment Document And Classification:</b>                   | Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall   |
| <b>Thread Series Designator:</b>  | Unjf   |
| <b>Specification/standard Data:</b>                                     | 80205-nas6603 Professional/Industrial Association Standard   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6603DH4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.