

Description

Fastener Length: 2-15/32", Thread: 10-32, Thread Length: 11/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6603H34
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-386-1347
Schedule B:	7318.15.8085
ECCN:	9A991



\* See page 2 for technical characteristics

## P/N NAS6603H34 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.345 Inches Nominal
<b>Fastener Length:</b>	2.470 Inches Nominal
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.110 Inches Nominal
<b>Width Between Flats:</b>	0.367 Inches Minimum And 0.376 Inches Maximum
<b>Grip Diameter:</b>	0.186 Inches Minimum And 0.190 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	2.125 Inches Nominal
<b>Hole Quantity:</b>	3
<b>Hole Type:</b>	Drilled
<b>Thread Quantity Per Inch:</b>	32
<b>Hole Configuration Style:</b>	Hexagon Corners
<b>Special Features:</b>	Shall Be In Accordance With All Requirements As Specified In National Aerospace Standard Nas 6603 Through 6620
<b>Material:</b>	Steel Comp E4340 Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas6603 Professional/industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6603H34> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.