

Description

Fastener Length: 2-19/32", Thread: 10-32, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6603H36
Minimum Qty (MOQ):	10 EA
NSN:	5306-01-386-1394
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS6603H36 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.345 Inches Nominal
Fastener Length:	2.595 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.110 Inches Nominal
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Grip Diameter:	0.186 Inches Minimum And 0.190 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	2.250 Inches Nominal
Hole Quantity:	3
Hole Type:	Drilled
Thread Quantity Per Inch:	32
Hole Configuration Style:	Hexagon Corners
Special Features:	Shall Be In Accordance With All Requirements As Specified In National Aerospace Standard Nas 6603 Through 6620
Material:	Steel Comp E4340 Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6603 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6603H36> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.