

P/N NAS6603L5

Description

Fastener Length: 43/64", Thread: 10-32, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS6603L5
Minimum Qty (MOQ): 5 EA

NSN: 5306-01-448-9426

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS6603L5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.345 Inches Nominal
Fastener Length:	0.642 Inches Minimum And 0.672 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Width Between Flats:	0.642 Inches Minimum And 0.643 Inches Maximum
Locking Feature:	Patch Locking Feature Or Pellet Locking Feature Or Strip Locking Feature
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Comp 8740 Fastener Or Steel Comp 4140 Fastener Or Steel Comp 4340 Fastener
Surface Treatment:	Cadmium Fastener And Chromate Fastener
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6603 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6603L5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.