

Description

Fastener Length: 1-1/8", Thread: 1/4-28, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS660411X
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-121-8482
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS6604-11X Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.400 Inches Minimum And 0.450 Inches Maximum
Fastener Length:	1.098 Inches Minimum And 1.128 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.429 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.2641 Inches Minimum And 0.2651 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.678 Inches Minimum And 0.698 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6604 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6604-11X> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.