

P/N NAS6604-20

Description

length: 1.675", grip: 1.250", thread: 1/4-28, hex head, tension, long thread, cadmium plated alloy steel, NAS6604 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS660420

Minimum Qty (MOQ): 25

NSN: 5306-01-186-1222

Schedule B: 7318.15.2095

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS6604-20 Specifications

3a
Right-hand
0.400 Inches Minimum And 0.450 Inches Maximum
1.660 Inches Minimum And 1.690 Inches Maximum
Dished Hexagon
0.125 Inches Minimum And 0.140 Inches Maximum
0.429 Inches Minimum And 0.439 Inches Maximum
0.2485 Inches Minimum And 0.2495 Inches Maximum
95000 Pounds Per Square Inch
0.250 Inches
1.240 Inches Minimum And 1.260 Inches Maximum
28
160000 Pounds Per Square Inch
36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
32.0 Microinches Bearing Surface Of Head
32.0 Microinches Grip
32.0 Microinches Threads
Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response Overall
Unjf
80205-nas6604 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6604-20 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.