

Description

length: 0.613", grip: 0.188", thread: 1/4-28, hex head, tension, long thread, cadmium plated alloy steel, NAS6604 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS66043 |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5306-01-142-9400 |
| Schedule B: | 7318.15.2095 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N NAS6604-3 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.400 Inches Minimum And 0.450 Inches Maximum |
| Fastener Length: | 0.598 Inches Minimum And 0.628 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.125 Inches Minimum And 0.140 Inches Maximum |
| Width Between Flats: | 0.429 Inches Minimum And 0.439 Inches Maximum |
| Grip Diameter: | 0.2485 Inches Minimum And 0.2495 Inches Maximum |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.178 Inches Minimum And 0.198 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Steel Comp E4340 Overall Or Steel Comp 8740 Overall |
| Material Document And Classification: | Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6604 Professional/Industrial Association Standard |

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6604-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.