

P/N NAS6604-32

Description

length: 2.425", grip: 2.000", thread: 1/4-28, hex head, tension, long thread, cadmium plated alloy steel, NAS6604 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS660432

Minimum Qty (MOQ): 20

NSN: 5306-01-133-7918

Schedule B: 7318.15.2095

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS6604-32 Specifications

3a
Right-hand
0.425 Inches Minimum
2.410 Inches Minimum And 2.440 Inches Maximum
Dished Hexagon
0.125 Inches Minimum And 0.140 Inches Maximum
0.429 Inches Minimum And 0.439 Inches Maximum
0.2485 Inches Minimum And 0.2495 Inches Maximum
0.250 Inches
1.990 Inches Minimum And 2.010 Inches Maximum
28
160000 Pounds Per Square Inch
32.0 Microinches Grip
32.0 Microinches Threads
Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416,type 2class 2 Fed Spec Single Treatment Response Overall
Unjf
80205-nas6603 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6604-32 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6604-32 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6604-32 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6604-32 and selecting the quantity you want then