

**Description**

Fastener Length: 2-63/64", Thread: 1/4-28, Thread Length: 27/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS660439
Minimum Qty (MOQ):	15 EA
NSN:	5306-01-576-0017
Schedule B:	7318.15.8085
ECCN:	9A991

NO IMAGE  
AVAILABLE

## P/N NAS6604-39 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.425 Inches Nominal
<b>Fastener Length:</b>	2.972 Inches Minimum And 3.002 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.125 Inches Minimum And 0.140 Inches Maximum
<b>Width Between Flats:</b>	0.429 Inches Minimum And 0.439 Inches Maximum
<b>Grip Diameter:</b>	0.248 Inches Minimum And 0.249 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	2.422 Inches Minimum And 2.452 Inches Maximum
<b>Thread Quantity Per Inch:</b>	28
<b>Part Name Assigned By Controlling Agency:</b>	Bolt, Tension, Hex Head, Close Tolerance, Alloy Steel, Long Thread, Reduced Major Diameter, Non-locking, 160 Ksi FtU
<b>Material:</b>	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Ams6349 Assn Std Single Material Response Overall Or Ams6382 Assn Std Single Material Response Overall Or Ams6415 Assn Std Single Material Response Overall Or Ams6484 Assn Std Single Material Response Overall Or Ams6322 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Ams-qq-p-416, Type II, Class 2 Assn Std Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6604-39> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.