

Description

Fastener Length: 2-63/64", Thread: 1/4-28, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS660439
Minimum Qty (MOQ):	15 EA
NSN:	5306-01-576-0017
Schedule B:	7318.15.8085
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N NAS6604-39 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.425 Inches Nominal
Fastener Length:	2.972 Inches Minimum And 3.002 Inches Maximum
Head Style:	Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.429 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.248 Inches Minimum And 0.249 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	2.422 Inches Minimum And 2.452 Inches Maximum
Thread Quantity Per Inch:	28
Part Name Assigned By Controlling Agency:	Bolt, Tension, Hex Head, Close Tolerance, Alloy Steel, Long Thread, Reduced Major Diameter, Non-locking, 160 Ksi FtU
Material:	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Ams6349 Assn Std Single Material Response Overall Or Ams6382 Assn Std Single Material Response Overall Or Ams6415 Assn Std Single Material Response Overall Or Ams6484 Assn Std Single Material Response Overall Or Ams6322 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams-qq-p-416, Type II, Class 2 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6604-39> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.