

Description

Fastener Length: 2-63/64", Thread: 1/4-28, Thread Length: 27/64",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS660441
Minimum Qty (MOQ):	10
NSN:	5306-01-525-5487
Schedule B:	7318.15.8085
ECCN:	EAR99



P/N NAS6604-41 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.425 Inches Nominal
Fastener Length:	2.972 Inches Minimum And 3.002 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.429 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.2445 Inches Minimum And 0.2450 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	2.552 Inches Minimum And 2.572 Inches Maximum
Thread Quantity Per Inch:	28
Material:	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Ams6349 Assn Std 1st Material Response Overall Or Ams6382 Assn Std 2nd Material Response Overall Or Ams6322 Assn Std 3rd Material Response Overall Or Ams6415 Assn Std 4th Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Type 2, Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6608 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6604-41> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.