

P/N NAS6604-56

Military-Fasteners.com

### Description

Fastener Length: 3-15/16", Thread: 1/4-28, Thread Length: 7/16

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	NAS660456
Minimum Qty (MOQ):	10
NSN:	5306-01-234-9401
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# P/N NAS6604-56 Specifications

	2-
Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.400 Inches Minimum And 0.450 Inches Maximum
Fastener Length:	3.915 Inches Minimum And 3.940 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.429 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	3.490 Inches Minimum And 3.510 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2 Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6604 Professional/industrial Association Standard

## How to Order

Order this shear bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/shear+bolts/NAS6604-56</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.