

P/N NAS6604-58

Description

Fastener Length: 4-1/16", Thread: 1/4-28, Thread Length: 7/16

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS660458

Minimum Qty (MOQ):

NSN: 5306-01-313-1707

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N NAS6604-58 Specifications

3a
Right-hand
0.400 Inches Minimum And 0.450 Inches Maximum
4.035 Inches Minimum And 4.065 Inches Maximum
Dished Hexagon
0.125 Inches Minimum And 0.140 Inches Maximum
0.429 Inches Minimum And 0.439 Inches Maximum
0.2445 Inches Minimum And 0.2450 Inches Maximum
0.250 Inches
3.615 Inches Minimum And 3.635 Inches Maximum
28
160000 Pounds Per Square Inch
36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
32.0 Microinches Bearing Surface Of Head
32.0 Microinches Grip
32.0 Microinches Threads
Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416 Ty 2,cl 2 Fed Spec Single Treatment Response Overall
Unjf
80205-nas6604 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6604-58 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6604-58 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6604-58 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6604-58 and selecting the quantity you want then