

Description

Fastener Length: 1-15/64", Thread: 1/4-28, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6604C13
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-592-0529
Schedule B:	7318.15.8085
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N NAS6604C13 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.425 Inches Nominal
Fastener Length:	1.237 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.429 Nominal Mils And 0.439 Nominal Centimeters
Grip Diameter:	0.2485 Nominal Mils And 0.2495 Nominal Centimeters
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.802 Nominal Mils And 0.822 Nominal Centimeters
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Bolt,hex Head,close Tolerance,alloy Steel,long Thread
Material:	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6604C13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.