

Description

Fastener Length: 1-1/4", Thread: 1/4-28, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS6604CD13 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-143-5034 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS6604CD13 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.400 Inches Minimum And 0.450 Inches Maximum |
| Fastener Length: | 1.222 Inches Minimum And 1.252 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.125 Inches Minimum And 0.140 Inches Maximum |
| Width Between Flats: | 0.429 Inches Minimum And 0.439 Inches Maximum |
| Grip Diameter: | 0.2485 Inches Minimum And 0.2495 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.802 Inches Minimum And 0.822 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 1.034 Inches Minimum First Hole And 1.084 Inches Maximum First Hole |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Steel Comp E4340 Overall Or Steel Comp 8740 Overall |
| Material Document And Classification: | Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall |
| Surface Treatment: | Cadmium Threads And Chromate Threads |
| Surface Treatment: | Chromium Grip |
| Surface Treatment: | Cadmium Head And Chromate Head |
| Surface Treatment Document And Classification: | Qq-c-320 Class 2 Fed Spec Single Treatment Response Grip |
| Surface Treatment Document And Classification: | Qq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response Threads |
| Surface Treatment Document And Classification: | Qq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response Head |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6604 Professional/Industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6604CD13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.