

Description

length: 1.30", grip: 0.875", thread: 1/4-28, hex head, drilled shank, tension, long thread, cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS6604D14 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5306-01-308-2849 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS6604D14 Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.425 Inches Nominal |
| Fastener Length: | 1.285 Inches Minimum And 1.315 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.125 Inches Minimum And 0.140 Inches Maximum |
| Width Between Flats: | 0.430 Inches Minimum And 0.439 Inches Maximum |
| Grip Diameter: | 0.2481 Inches Minimum And 0.2487 Inches Maximum |
| Single Shear Strength: | 95000 Pounds Per Square Inch |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.865 Inches Minimum And 0.885 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Material: | Steel Comp 4340 Overall |
| Material Document And Classification: | Mil-s-5000 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6604d14 Professional/industrial Association Standard |

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6604D14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.