

**Description**

length: 1.363", grip: 0.938", thread: 1/4-28, hex head, drilled shank, tension, long thread, cadmium plated alloy steel, NAS6604 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS6604D15
Minimum Qty (MOQ):	10
NSN:	5306-01-274-5392
Schedule B:	7318.15.2095
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS6604D15 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.425 Inches Nominal
<b>Fastener Length:</b>	1.348 Inches Minimum And 1.378 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.125 Inches Minimum And 0.140 Inches Maximum
<b>Width Between Flats:</b>	0.430 Inches Minimum And 0.439 Inches Maximum
<b>Grip Diameter:</b>	0.2481 Inches Minimum And 0.2487 Inches Maximum
<b>Single Shear Strength:</b>	95000 Pounds Per Square Inch
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	0.928 Inches Minimum And 0.948 Inches Maximum
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Material:</b>	Steel Comp 4340 Overall
<b>Material Document And Classification:</b>	Mil-s-5000 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas6604d15 Professional/industrial Association Standard

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6604D15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.