

P/N NAS6604D28

Description

Fastener Length: 2-3/16", Thread: 1/4-28, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS6604D28

Minimum Qty (MOQ): 10 EA

NSN: 5306-01-329-6505

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS6604D28 Specifications

Thread Direction: Right-hand Thread Length: 0.400 Inches Minimum And 0.450 Inches Maximum Fastener Length: 2.160 Inches Minimum And 2.190 Inches Maximum Head Style: Dished Hexagon Head Helght: 0.125 Inches Minimum And 0.140 Inches Maximum Width Between Flats: 0.429 Inches Minimum And 0.439 Inches Maximum Width Between Flats: 0.429 Inches Minimum And 0.439 Inches Maximum Grip Diameter: 0.245 Inches Minimum And 0.2450 Inches Maximum Shank Unthreaded Hole Diameter: 0.250 Inches Minimum First Hole And 0.086 Inches Maximum First Hole Nominal Thread Diameter: 0.250 Inches Grip Length: 1.740 Inches Minimum And 1.760 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 1.972 Inches Minimum Pirst Hole And 2.022 Inches Maximum First Hole Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Minis-5000 Mil Spec 1st Material Response Overall Or Minis-6049 Mil Spec 2nd Material Response Overall Or Ame6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: 0,9-p-416 Ty 2,cl 2 Fed Spec Single Treatment Response Overall	Thread Class:	3a
Thread Length: 0.400 Inches Minimum And 0.450 Inches Maximum Fastener Length: 2.160 Inches Minimum And 2.190 Inches Maximum Head Style: Dished Hexagon 1.25 Inches Minimum And 0.140 Inches Maximum Width Between Flats: 0.429 Inches Minimum And 0.439 Inches Maximum Width Between Flats: 0.429 Inches Minimum And 0.439 Inches Maximum Grip Diameter: 0.2445 Inches Minimum And 0.2450 Inches Maximum Shank Unthreaded Hole Diameter: 0.250 Inches Minimum First Hole And 0.086 Inches Maximum First Hole Nominal Thread Diameter: 0.250 Inches Grip Length: 1.740 Inches Minimum And 1.760 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Thread Series Designator: Unjf		
Fastener Length: 2.160 Inches Minimum And 2.190 Inches Maximum Head Style: Dished Hexagon Head Height: 0.125 Inches Minimum And 0.140 Inches Maximum Width Between Flats: 0.429 Inches Minimum And 0.439 Inches Maximum Grip Diameter: 0.2445 Inches Minimum And 0.439 Inches Maximum Shank Unthreaded Hole Diameter: 0.076 Inches Minimum And 0.086 Inches Maximum First Hole Nominal Thread Diameter: 0.250 Inches Grip Length: 1.740 Inches Minimum And 1.760 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 16000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 3.972 Inches Minimum First Hole And 2.022 Inches Maximum First Hole Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material Document And Classification: 32.0 Microinches Threads Material Document And Classification: Americal And Chromate Overall Or Mili-s-6049 Mil Spec 2nd Material Response Overall Or Mili-s-6049 Mil Spec 2nd Material Response Overall Or Mili-s-6049 Mi		
Head Style: Dished Hexagon Head Height: 0.125 Inches Minimum And 0.140 Inches Maximum Width Between Flats: 0.429 Inches Minimum And 0.439 Inches Maximum Grip Diameter: 0.2445 Inches Minimum And 0.2450 Inches Maximum Shank Unthreaded Hole Diameter: 0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole Nominal Thread Diameter: 0.250 Inches Grip Length: 1.740 Inches Minimum And 1.760 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 3.20 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Over	Thread Length:	0.400 Inches Minimum And 0.450 Inches Maximum
Head Height: 0.125 Inches Minimum And 0.140 Inches Maximum Width Between Flats: 0.429 Inches Minimum And 0.439 Inches Maximum Grip Diameter: 0.2445 Inches Minimum And 0.2450 Inches Maximum Shank Unthreaded Hole Diameter: 0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole Nominal Thread Diameter: 0.250 Inches Grip Length: 1.740 Inches Minimum And 1.760 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 1.972 Inches Minimum First Hole And 2.022 Inches Maximum First Hole Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mili-s-5000 Mil Spec 1st Material Response Overall Or Mili-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Or Mili-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Or Mili-s-6049 Mili-s-6049 Mili Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Or Mili-s-6049 Mili Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Or Ams64324 Assn Std 2nd Material Response Overall Or Ams64344 Assn Std 2nd Material Respo	Fastener Length:	2.160 Inches Minimum And 2.190 Inches Maximum
Width Between Flats: 0.429 Inches Minimum And 0.439 Inches Maximum 0.2455 Inches Minimum And 0.2450 Inches Maximum Shank Unthreaded Hole Diameter: 0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole Nominal Thread Diameter: 0.250 Inches Grip Length: 1.740 Inches Minimum And 1.760 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: Hardness Rating: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 32.9 Inches Minimum First Hole And 2.022 Inches Maximum First Hole Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Material Document And Classification: Mill-s-5000 Mil Spec 1st Material Response Overall Or Mill-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Thread Series Designator: Unjf	Head Style:	Dished Hexagon
Grip Diameter: 0.2445 Inches Minimum And 0.2450 Inches Maximum Shank Unthreaded Hole Diameter: 0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole Nominal Thread Diameter: 0.250 Inches Grip Length: 1.740 Inches Minimum And 1.760 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 1.972 Inches Minimum First Hole And 2.022 Inches Maximum First Hole Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416 Ty 2,cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unif	Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Shank Unthreaded Hole Diameter: 0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole Nominal Thread Diameter: 0.250 Inches Grip Length: 1.740 Inches Minimum And 1.760 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 1.972 Inches Minimum First Hole And 2.022 Inches Maximum First Hole Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416 Ty 2,cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Width Between Flats:	0.429 Inches Minimum And 0.439 Inches Maximum
Nominal Thread Diameter: Grip Length: 1.740 Inches Minimum And 1.760 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 31.972 Inches Minimum First Hole And 2.022 Inches Maximum First Hole Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: 32.0 Microinches Threads Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416 Ty 2,cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Grip Diameter:	0.2445 Inches Minimum And 0.2450 Inches Maximum
Grip Length: Thread Quantity Per Inch: Alternating Strength: Distance From Head Largest Bearing Surface To Shank Hole Center: Surface Finish: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Surface Treatment Document And Classification: Oq-p-416 Ty 2,cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Shank Unthreaded Hole Diameter:	0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
Thread Quantity Per Inch: Minimum Tensile Strength: 160000 Pounds Per Square Inch 160000 Pounds Per Square Inch 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 1.972 Inches Minimum First Hole And 2.022 Inches Maximum First Hole 1.972 Inches Minimum First Hole And 2.022 Inches Maximum First Hole Surface Finish: 32.0 Microinches Bearing Surface Of Head 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Thread Series Designator: Unjf	Nominal Thread Diameter:	0.250 Inches
Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole Center:1.972 Inches Minimum First Hole And 2.022 Inches Maximum First HoleSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:5teel Comp E4340 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416 Ty 2,cl 2 Fed Spec Single Treatment Response OverallThread Series Designator:Unjf	Grip Length:	1.740 Inches Minimum And 1.760 Inches Maximum
Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: \$1.972 Inches Minimum First Hole And 2.022 Inches Maximum First Hole Surface Finish: \$2.0 Microinches Bearing Surface Of Head Surface Finish: \$32.0 Microinches Grip 32.0 Microinches Threads Material: \$2.0 Microinches Threads Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: \$2.0 Microinches Threads Steel Comp E4340 Overall Or Steel Comp 8740 Overall Ams6322 Assn Std 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment Document And Classification: Qq-p-416 Ty 2,cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Thread Quantity Per Inch:	28
Distance From Head Largest Bearing Surface To Shank Hole Center: Surface Finish: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Distance Treatment Document And Classification: Unjf Surface Treatment Document And Classification: Unjf	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Shank Hole Center: Surface Finish: Surface Finish: 32.0 Microinches Bearing Surface Of Head 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Surface Treatment Document And Classification: And Classification: Qq-p-416 Ty 2,cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Surface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Steel Comp E4340 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416 Ty 2,cl 2 Fed Spec Single Treatment Response OverallThread Series Designator:Unjf	Distance From Head Largest Bearing Surface To Shank Hole Center:	1.972 Inches Minimum First Hole And 2.022 Inches Maximum First Hole
Surface Finish: Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416 Ty 2,cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Surface Finish:	32.0 Microinches Bearing Surface Of Head
Material:Steel Comp E4340 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416 Ty 2,cl 2 Fed Spec Single Treatment Response OverallThread Series Designator:Unjf	Surface Finish:	32.0 Microinches Grip
Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416 Ty 2,cl 2 Fed Spec Single Treatment Response Overall Unjf	Surface Finish:	32.0 Microinches Threads
Material Document And Classification: Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416 Ty 2,cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Surface Treatment Document And Classification: Qq-p-416 Ty 2,cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Material Document And Classification:	
Thread Series Designator: Unjf	Surface Treatment:	Cadmium Overall And Chromate Overall
-	Surface Treatment Document And Classification:	Qq-p-416 Ty 2,cl 2 Fed Spec Single Treatment Response Overall
Specification/standard Data: 80205-nas6604 Professional/industrial Association Standard	Thread Series Designator:	Unjf
	Specification/standard Data:	80205-nas6604 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6604D28 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6604D28 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6604D28 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6604D28 and selecting the quantity you want then click "add to cart".