

Description

Fastener Length: 4-35/64", Thread: 1/4-28, Thread Length: 27/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6604D66
Minimum Qty (MOQ):	10
NSN:	5306-01-471-4131
Schedule B:	7318.15.2010
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS6604D66 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.425 Inches Nominal
Fastener Length:	4.550 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Width Between Flats:	0.429 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
End Item Identification:	F-15 N.I.g.
Nominal Thread Diameter:	0.250 Inches
Grip Length:	4.115 Inches Minimum And 4.135 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	4.392 Inches Nominal First Hole
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Ams 6415 Assn Std 2nd Material Response Overall Or Mil-s-500 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type II,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6604 Professional/Industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6604D66> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.