

**Description**

Fastener Length: 1-1/8", Thread: 1/4-28, Thread Length: 27/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS6604DH11
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-438-8252
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS6604DH11 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.4250 Inches Nominal
<b>Fastener Length:</b>	1.0980 Inches Minimum And 1.1280 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.1250 Inches Minimum And 0.1400 Inches Maximum
<b>Width Between Flats:</b>	0.4290 Inches Minimum And 0.4390 Inches Maximum
<b>Grip Diameter:</b>	0.2485 Inches Minimum And 0.2495 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.2500 Inches
<b>Grip Length:</b>	0.6780 Inches Minimum And 0.6980 Inches Maximum
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Material:</b>	Steel Comp 4340 Overall Or Steel Comp 8740 Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas6604dh11 Professional/industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6604DH11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.