



Military-Fasteners.com

P/N NAS6604DH11

Description

Fastener Length: 1-1/8", Thread: 1/4-28, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6604DH11
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-438-8252
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS6604DH11 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.4250 Inches Nominal
Fastener Length:	1.0980 Inches Minimum And 1.1280 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.1250 Inches Minimum And 0.1400 Inches Maximum
Width Between Flats:	0.4290 Inches Minimum And 0.4390 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Nominal Thread Diameter:	0.2500 Inches
Grip Length:	0.6780 Inches Minimum And 0.6980 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6604dh11 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6604DH11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.