

P/N NAS6604H16

Description

length: 1.425", grip: 1.000", thread: 1/4-28, hex head, drilled head, tension, long thread, cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS6604H16

Minimum Qty (MOQ): 5

NSN: 5306-01-355-2690

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS6604H16 Specifications

3a
Right-hand
0.425 Inches Nominal
1.410 Inches Minimum And 1.440 Inches Maximum
Dished Hexagon
0.125 Inches Minimum And 0.140 Inches Maximum
0.429 Inches Minimum And 0.439 Inches Maximum
0.046 Inches Minimum And 0.056 Inches Maximum
0.2485 Inches Minimum And 0.2495 Inches Maximum
0.250 Inches
0.990 Inches Minimum And 1.010 Inches Maximum
3
Drilled
28
160000 Pounds Per Square Inch
Hexagon Corners
32.0 Microinches Grip32.0 Microinches Threads32.0 Microinches Fastener
Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall
Cadmium Overall And Chromate Overall
Qq-d-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall
Unjf
80205-nas6604 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6604H16 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.