

Description

length: 1.987", grip: 1.562", thread: 1/4-28, hex head - drilled head - tension - long thread - cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6604H25
Minimum Qty (MOQ):	2
NSN:	5306-01-231-8935
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS6604H25 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.425 Inches Nominal
Fastener Length:	1.972 Inches Minimum And 2.002 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.429 Inches Minimum And 0.439 Inches Maximum
Hole Diameter:	0.046 Inches Minimum And 0.056 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	1.552 Inches Minimum And 1.572 Inches Maximum
Hole Quantity:	3
Hole Type:	Drilled
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hole Configuration Style:	Hexagon Corners
Material:	Steel Comp 4340 And Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416a,ty2,cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6604 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6604H25> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.