

P/N NAS6605-1

Description

length: 0.531", grip: 0.062", thread: 5/16-24, hex head, tension, long thread, cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS66051

Minimum Qty (MOQ): 20

NSN: 5306-01-309-8544

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS6605-1 Specifications

3a
Right-hand
0.444 Inches Minimum And 0.494 Inches Maximum
0.516 Inches Minimum And 0.546 Inches Maximum
Dished Hexagon
0.156 Inches Minimum And 0.171 Inches Maximum
0.492 Inches Minimum And 0.502 Inches Maximum
0.3110 Inches Minimum And 0.3120 Inches Maximum
0.312 Inches
0.052 Inches Minimum And 0.072 Inches Maximum
24
160000 Pounds Per Square Inch
36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
32.0 Microinches Bearing Surface Of Head
32.0 Microinches Grip
32.0 Microinches Threads
Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416 Ty 2,cl 2 Fed Spec Single Treatment Response Overall
Unjf
80205-nas6605 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6605-1 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6605-1 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6605-1 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6605-1 and selecting the quantity you want then click "add to cart".