

**Description**

NAS6605-38 Shoulder Bolt

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS660538                                 |
| Minimum Qty (MOQ):      | 10  |
| NSN:                    | 5306-01-317-6685                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS6605-38 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.444 Inches Minimum And 0.494 Inches Maximum                                 |
| <b>Fastener Length:</b>                               | 2.829 Inches Minimum And 2.859 Inches Maximum                                 |
| <b>Head Style:</b>                                    | Dished Hexagon  |
| <b>Head Height:</b>                                   | 0.156 Inches Minimum And 0.171 Inches Maximum                                 |
| <b>Width Between Flats:</b>                           | 0.492 Inches Minimum And 0.502 Inches Maximum                                 |
| <b>Shoulder Diameter:</b>                             | 0.3266 Inches Minimum First Shoulder And 0.3276 Inches Maximum First Shoulder |
| <b>Shoulder Length:</b>                               | 2.365 Inches Minimum First Shoulder And 2.385 Inches Maximum First Shoulder   |
| <b>Nominal Thread Diameter:</b>                       | 0.312 Inches  |
| <b>Thread Quantity Per Inch:</b>                      | 24  |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch   |
| <b>Hardness Rating:</b>                               | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall           |
| <b>Shoulder Shape:</b>                                | Round First Shoulder  |
| <b>Material:</b>                                      | Steel Comp 4340 Overall   |
| <b>Material Document And Classification:</b>          | Mil-s-5000 Mil Spec Single Material Response Overall                          |
| <b>Surface Treatment:</b>                             | Cadmium Overall   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416a,ty 2,c12 Fed Spec Single Treatment Response Overall                 |
| <b>Thread Series Designator:</b>                      | Unjf  |
| <b>Specification/standard Data:</b>                   | 80205-nas6605-38 Professional/industrial Association Standard                 |

## How to Order

Order this shoulder bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shoulder+bolts/NAS6605-38> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.