

Description

NAS6605-58 Close Tolerance Bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS660558
Minimum Qty (MOQ):	1
NSN:	5306-01-502-8789
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS6605-58 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.469 Inches Nominal
Fastener Length:	4.079 Inches Minimum And 4.109 Inches Maximum
Head Style:	Hexagon
Head Height:	0.141 Inches Minimum And 0.171 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Grip Diameter:	0.311 Inches Minimum And 0.312 Inches Maximum
Point Diameter:	0.302 Inches Minimum And 0.306 Inches Maximum
Point Style:	Flat
Nominal Thread Diameter:	0.312 Inches
Grip Length:	3.615 Inches Minimum And 3.635 Inches Maximum
Thread Quantity Per Inch:	24
Material:	Steel Comp 4140 Overall And Steel Comp 4340 Overall And Steel Comp E4340 Overall And Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall And Ams6415 Assn Std 2nd Material Response Overall And Mil-s-5000 Mil Spec 3rd Material Response Overall And Mil-s-6044 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Type II, Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS6605-58> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.