

P/N NAS6605-58

Description

NAS6605-58 Close Tolerance Bolt

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS660558

Minimum Qty (MOQ):

NSN: 5306-01-502-8789

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS6605-58 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.469 Inches Nominal
Fastener Length:	4.079 Inches Minimum And 4.109 Inches Maximum
Head Style:	Hexagon
Head Height:	0.141 Inches Minimum And 0.171 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Grip Diameter:	0.311 Inches Minimum And 0.312 Inches Maximum
Point Diameter:	0.302 Inches Minimum And 0.306 Inches Maximum
Point Style:	Flat
Nominal Thread Diameter:	0.312 Inches
Grip Length:	3.615 Inches Minimum And 3.635 Inches Maximum
Thread Quantity Per Inch:	24
Material:	Steel Comp 4140 Overall And Steel Comp 4340 Overall And Steel Comp E4340 Overall And Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall And Ams6415 Assn Std 2nd Material Response Overall And Mil-s-5000 Mil Spec 3rd Material Response Overall And Mil-s-6044 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Type Ii, Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this close tolerance bolt from our inventory online by visiting https://military-fasteners.com/bolts/close+tolerance+bolts/NAS6605-58 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/close+tolerance+bolts/NAS6605-58 and selecting the