

Description

length: 1.344", grip: 0.875", thread: 5/16-24, hex head - drilled shank - tension - long thread - cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS6605D14 |
| Minimum Qty (MOQ): | 4 |
| NSN: | 5306-01-438-8251 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS6605D14 Specifications

| | |
|-------------------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.4690 Inches Nominal |
| Fastener Length: | 1.3290 Inches Minimum And 1.3590 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.1560 Inches Minimum And 0.1710 Inches Maximum |
| Width Between Flats: | 0.4920 Inches Minimum And 0.5020 Inches Maximum |
| Grip Diameter: | 0.3110 Inches Minimum And 0.3120 Inches Maximum |
| Nominal Thread Diameter: | 0.3125 Inches |
| Grip Length: | 0.8650 Inches Minimum And 0.8850 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Material: | Steel Comp 4340 Overall Or Steel Comp 8740 Overall |
| Surface Treatment: | Cadmium Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6605d14 Professional/Industrial Association Standard |

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6605D14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.