

Description

length: 1.657", grip: 1.188", thread: 5/16-24, hex head, drilled shank, tension, long thread, cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6605D19
Minimum Qty (MOQ):	10
NSN:	5306-01-438-8253
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS6605D19 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.4690 Inches Nominal
Fastener Length:	1.6420 Inches Minimum And 1.6720 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.1560 Inches Minimum And 0.1710 Inches Maximum
Width Between Flats:	0.4920 Inches Minimum And 0.5020 Inches Maximum
Grip Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Nominal Thread Diameter:	0.3125 Inches
Grip Length:	1.1780 Inches Minimum And 1.1980 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6605d19 Professional/Industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6605D19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.