

**Description**

length: 1.657", grip: 1.188", thread: 5/16-24, hex head, drilled shank, tension, long thread, cadmium plated alloy steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS6605D19
Minimum Qty (MOQ):	10
NSN:	5306-01-438-8253
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N NAS6605D19 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.4690 Inches Nominal
<b>Fastener Length:</b>	1.6420 Inches Minimum And 1.6720 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.1560 Inches Minimum And 0.1710 Inches Maximum
<b>Width Between Flats:</b>	0.4920 Inches Minimum And 0.5020 Inches Maximum
<b>Grip Diameter:</b>	0.3110 Inches Minimum And 0.3120 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.3125 Inches
<b>Grip Length:</b>	1.1780 Inches Minimum And 1.1980 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Material:</b>	Steel Comp 4340 Overall Or Steel Comp 8740 Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas6605d19 Professional/Industrial Association Standard

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6605D19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.