

# P/N NAS6605D21

Military-Fasteners.com

### Description

length: 1.781", grip: 1.312", thread: 5/16-24, hex head, drilled shank, tension, long thread, cadmium plated alloy steel

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

#### Alternate Part Numbers

10.00000 210	
SKU / Model:	NAS6605D21
Minimum Qty (MOQ):	5
NSN:	5306-01-332-2165
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



### P/N NAS6605D21 Specifications

Thread Direction:Right-handThread Length:0.469 Inches NominalFasteer Length:1.766 Inches Minimum And 1.796 Inches MaximumHead Style:Dished HexagonHead Height:0.156 Inches Minimum And 0.171 Inches MaximumWidth Between Flats:0.492 Inches Minimum And 0.502 Inches MaximumGrip Diameter:0.310 Inches Minimum And 0.320 Inches MaximumShank Unthreaded Hole Diameter:0.312 Inches Minimum And 0.320 Inches MaximumSominal Thread Diameter:0.312 Inches Minimum And 0.320 Inches MaximumGrip Length:1.302 Inches Minimum And 0.320 Inches MaximumThread Quantity Per Inch:24Minimum Tensile Strength:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Kole Center:2.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterialStel Comp E4340 Overall Or SHI-6040 Mil-6049 Mil Spec 2nd Material Response Overall Or Mil-5000 Mil Spec 1st Material Response Overall Or Mil-6049 Mil Spec 2nd Material Response Overall Or Mis-5000 Mil Spec 1st Material Response Overall Or Mil-6049 Mil Spec 2nd Material Response OverallSurface Treatment Document And Classification:Qa+116,17,27,27 Ef Spec Single Treatment Response OverallSurface Teatment Document And Classification:Qi-706052 Professional/industrial Association Standard	Thread Class:	За
Thread Length:0.469 Inches NominalFastener Length:1.766 Inches Minimum And 1.796 Inches MaximumHead Style:Dished HexagonHead Height:0.156 Inches Minimum And 0.171 Inches MaximumWidth Between Flats:0.492 Inches Minimum And 0.502 Inches MaximumGrip Diameter:0.3110 Inches Minimum And 0.3120 Inches MaximumShak Unthreaded Hole Diameter:0.312 Inches Minimum First Hole And 0.086 Inches Maximum First HoleNominal Thread Diameter:0.312 InchesGrip Length:1.302 Inches Minimum And 1.322 Inches MaximumThread Quantity Per Inch:24Minimum Tensile Strength:1.6000 Pounds Per Square InchHardness Rating:0.60 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface Ton2.0 Microinches Bearing Surface Of HeadSurface Finish:3.0 Microinches Rearing Surface Of HeadSurface Finish:2.0 Microinches ThreadsMaterial Encoument And Classification:Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Content Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Materi	Thread Direction:	Right-hand
Pastener Length:1.766 Inches Minimum And 1.796 Inches MaximumHead Style:Dished HexagonHead Height:0.156 Inches Minimum And 0.171 Inches MaximumWidth Between Flats:0.492 Inches Minimum And 0.3120 Inches MaximumGrip Diameter:0.310 Inches Minimum And 0.3120 Inches MaximumShank Unthreaded Hole Diameter:0.312 Inches Minimum First Hole And 0.066 Inches Maximum First HoleNominal Thread Diameter:0.312 Inches Minimum First Hole And 0.066 Inches Maximum First HoleNominal Thread Diameter:0.312 Inches Minimum And 1.322 Inches MaximumGrip Length:1.302 Inches Minimum And 1.322 Inches MaximumThread Quartity Per Inch:24Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:0.50 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole Center:3.00 Incrionches Bearing Surface Of HeadSurface Finish:3.20 Microinches GripSurface Finish:3.20 Microinches GripSurface Finish:3.20 Microinches ThreadsMaterial Document And Classification:Kell Comp E4340 Overall Or Steel Comp 8740 Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or M	Thread Length:	
Head Style:Dished HexagonHead Height:0.156 Inches Minimum And 0.171 Inches MaximumWidth Between Flats:0.492 Inches Minimum And 0.502 Inches MaximumGrip Diameter:0.3110 Inches Minimum And 0.3120 Inches MaximumShank Unthreaded Hole Diameter:0.076 Inches Minimum First Hole And 0.086 Inches Maximum First HoleNominal Thread Diameter:0.312 InchesGrip Length:1.302 Inches Minimum And 1.322 Inches MaximumThread Quantity Per Inch:4Minimum Tensile Strength:1.60000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole Center:1.600 Inches Nominal First HoleSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterialSteel Comp E4340 Overall Or Steel Comp 8740 OverallMaterial:Steel Comp E4340 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:0q:p-416;ty 2,cl 2 Fed Spec Single Treatment Response OverallSurface Treatment:0q:p-416;ty 2,cl 2 Fed Spec Single Treatment Response OverallThread Classification:0q:p-416;ty 2,cl 2 Fed Spec Single Treatment Response OverallThread Series Designator:Unif		1.766 Inches Minimum And 1.796 Inches Maximum
Head Height:0.156 Inches Minimum And 0.171 Inches MaximumWidth Between Flats:0.492 Inches Minimum And 0.502 Inches MaximumGrip Dameter:0.3110 Inches Minimum Int And 0.3120 Inches Maximum First HoleShak Unthreaded Hole Diameter:0.076 Inches Minimum First Hole And 0.086 Inches Maximum First HoleNominal Thread Diameter:0.312 InchesOrrip Length:1.302 Inches Minimum And 1.322 Inches Maximum First HoleThread Quantity Per Inch:2Ad4Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole Center:1.600 Inches Nominal First HoleSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams522 Assn Std 2nd Material Response Overall Or Material Response Overall And Chromate OverallSurface Treatment:Cadmium Overall And Chromate OverallFuread Series Designator:Unjf	_	Dished Hexagon
Width Between Flats:0.492 Inches Minimum And 0.502 Inches MaximumGrip Diameter:0.3110 Inches Minimum And 0.3120 Inches MaximumShank Unthreaded Hole Diameter:0.076 Inches Minimum First Hole And 0.086 Inches Maximum First HoleNominal Thread Diameter:0.312 InchesGrip Length:1.302 Inches Minimum And 1.322 Inches MaximumThread Quantity Per Inch:24Minimum Tensile Strength:16000 Pounds Per Square InchBistance From Head Largest Bearing Surface To Shank Hole Center:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface OripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches Studi In S	-	
Shank Unthreaded Hole Diameter:0.076 Inches Minimum First Hole And 0.086 Inches Maximum First HoleNominal Thread Diameter:0.312 InchesGrip Length:1.302 Inches Minimum And 1.322 Inches MaximumThread Quantity Per Inch:24Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:0.6.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole Center:1.600 Inches Nominal First HoleSurface Frinish:2.0. Microinches Bearing Surface Of HeadSurface Finish:2.0. Microinches GripSurface Finish:2.0. Microinches GripSurface Finish:2.0. Microinches ThreadsMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:0.010-0.000 Mil Spec 1st Grip Streatment Response OverallSurface Treatment:0.000 Mil Spec 1st Grip Streatment Response OverallMaterial Response Overall0.0000 Mil Spec 1st Grip Streatment Response Overall <th>-</th> <th>0.492 Inches Minimum And 0.502 Inches Maximum</th>	-	0.492 Inches Minimum And 0.502 Inches Maximum
Shank Unthreaded Hole Diameter:0.076 Inches Minimum First Hole And 0.086 Inches Maximum First HoleNominal Thread Diameter:0.312 InchesGrip Length:1.302 Inches Minimum And 1.322 Inches MaximumThread Quantity Per Inch:24Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:0.6.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole Center:1.600 Inches Nominal First HoleSurface Frinish:2.0. Microinches Bearing Surface Of HeadSurface Finish:2.0. Microinches GripSurface Finish:2.0. Microinches GripSurface Finish:2.0. Microinches ThreadsMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:0.010-0.000 Mil Spec 1st Grip Streatment Response OverallSurface Treatment:0.000 Mil Spec 1st Grip Streatment Response OverallMaterial Response Overall0.0000 Mil Spec 1st Grip Streatment Response Overall <th>Grip Diameter:</th> <th>0.3110 Inches Minimum And 0.3120 Inches Maximum</th>	Grip Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Grip Length:1.302 Inches Minimum And 1.322 Inches MaximumThread Quantity Per Inch:24Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface Too Shank Hole Center:31.000 Inches Nominal First HoleSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Steel Comp E4340 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:0q-p-16,ty 2,cl 2 Fed Spec Single Treatment Response OverallThread Series Designator:Unif		0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
Thread Quantity Per Inch:24Minimum Tensile Strength:16000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole Center:1.600 Inches Nominal First HoleSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Steel Comp E4340 Overall Or Steel Comp 8740 OverallMaterial:Steel Comp E4340 Overall Or Steel Comp 8740 OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qr.p-416,ty 2,cl 2 Fed Spec Single Treatment Response OverallThread Series Designator:Unjf	Nominal Thread Diameter:	0.312 Inches
Thread Quantity Per Inch:24Minimum Tensile Strength:16000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole Center:1.600 Inches Nominal First HoleSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Steel Comp E4340 Overall Or Steel Comp 8740 OverallMaterial:Steel Comp E4340 Overall Or Steel Comp 8740 PoreallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:Outper-16,ty 2, cl 2 Fed Spec Single Treatment Response OverallThread Series Designator:Unjf	Grip Length:	1.302 Inches Minimum And 1.322 Inches Maximum
Hardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallDistance From Head Largest Bearing Surface To Shank Hole Center:1.600 Inches Nominal First HoleSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Steel Comp E4340 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Q-p-416,ty 2,cl 2 Fed Spec Single Treatment Response OverallThread Series Designator:Unjf	Thread Quantity Per Inch:	24
Distance From Head Largest Bearing Surface To Shank Hole Center:1.600 Inches Nominal First HoleSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Steel Comp E4340 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Q-p-416,ty 2,cl 2 Fed Spec Single Treatment Response OverallThread Series Designator:Unjf	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Shank Hole Center:1.000 Inches Nominal First HoleSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Steel Comp E4340 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall OrSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:0q-p-416,ty 2,cl 2 Fed Spec Single Treatment Response OverallUnjf	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Surface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Steel Comp E4340 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec		1.600 Inches Nominal First Hole
Surface Finish:32.0 Microinches ThreadsMaterial:Steel Comp E4340 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mines Overall Or Mines Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mines Overall Overall Overall Overall Overall Overall Overall OverallSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response OverallThread Series Designator:Unjf	Surface Finish:	32.0 Microinches Bearing Surface Of Head
Material:Steel Comp E4340 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response OverallThread Series Designator:Unjf	Surface Finish:	32.0 Microinches Grip
Material Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response OverallThread Series Designator:Unjf	Surface Finish:	32.0 Microinches Threads
Material Document And Classification: Ams6322 Assn Std 2nd Material Response Overall   Surface Treatment: Cadmium Overall And Chromate Overall   Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall   Thread Series Designator: Unjf	Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall   Thread Series Designator: Unjf	Material Document And Classification:	
Thread Series Designator: Unjf	Surface Treatment:	Cadmium Overall And Chromate Overall
	Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Specification/standard Data: 80205-nas6605 Professional/industrial Association Standard	Thread Series Designator:	Unjf
	Specification/standard Data:	80205-nas6605 Professional/industrial Association Standard

### How to Order

Order this shear bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/shear+bolts/NAS6605D21</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.