

# P/N NAS6605D22

Military-Fasteners.com

#### Description

length: 1.844", grip: 1.375", thread: 5/16-24, hex head - drilled shank - tension - long thread - cadmium plated alloy steel

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

#### **Additional Information**

SKU / Model:	NAS6605D22
Minimum Qty (MOQ):	4
NSN:	5306-01-467-8132



## P/N NAS6605D22 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.469 Inches Nominal
Fastener Length:	1.829 Inches Minimum And 1.859 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.156 Inches Minimum And 0.171 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Grip Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
Nominal Thread Diameter:	0.3125 Inches
Grip Length:	1.365 Inches Minimum And 1.385 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.653 Inches Minimum First Hole And 1.673 Inches Maximum First Hole
Material:	Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 3rd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Ty li, Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

### **How to Order**

Order this shear bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/shear+bolts/NAS6605D22</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.