

P/N NAS6605H2

Description

length: 0.594", grip: 0.125", thread: 5/16-24, hex head, drilled head, tension, long thread, cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS6605H2

Minimum Qty (MOQ): 10

NSN: 5306-01-322-8998

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS6605H2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.444 Inches Minimum And 0.494 Inches Maximum
Fastener Length:	0.579 Inches Minimum And 0.609 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.156 Inches Minimum And 0.171 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Hole Diameter:	0.070 Inches Minimum And 0.080 Inches Maximum
Grip Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.115 Inches Minimum And 0.135 Inches Maximum
Hole Quantity:	3
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Corners
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2,cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6605 Professional/industrial Association Standard

How to Order

