



Military-Fasteners.com

P/N NAS6605H23

Description

length: 1.907", grip: 1.438", thread: 5/16-24, hex head - drilled head - tension - long thread - cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6605H23
Minimum Qty (MOQ):	5
NSN:	5306-01-472-9577



* See page 2 for technical characteristics

P/N NAS6605H23 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.444 Inches Minimum And 0.494 Inches Maximum
Fastener Length:	1.892 Inches Minimum And 1.922 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.156 Inches Minimum And 1.171 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Hole Diameter:	0.070 Inches Minimum And 0.080 Inches Maximum
Grip Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	1.428 Inches Minimum And 1.448 Inches Maximum
Hole Quantity:	3
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hole Configuration Style:	Hexagon Corners
Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6605 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6605H23> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.