

P/N NAS6606-12

Description

length: 1.328", grip: 0.75", thread: 3/8-24, hex head, tension, long thread, cadmium plated alloy steel, NAS6606 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS660612

Minimum Qty (MOQ): 10

NSN: 5306-01-106-6703

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS6606-12 Specifications

| Thread Class: | 3a |
|--|---|
| Thread Direction: | Right-hand |
| Thread Length: | 0.553 Inches Minimum And 0.603 Inches Maximum |
| Fastener Length: | 1.313 Inches Minimum And 1.343 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.188 Inches Minimum And 0.203 Inches Maximum |
| Width Between Flats: | 0.554 Inches Minimum And 0.564 Inches Maximum |
| Grip Diameter: | 0.3735 Inches Minimum And 0.3745 Inches Maximum |
| Nominal Thread Diameter: | 0.375 Inches |
| Grip Length: | 0.740 Inches Minimum And 0.760 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Steel Comp E4340 Overall Or Steel Comp 8740 Overall |
| Material Document And Classification: | Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6606 Professional/industrial Association Standard |
| | |

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6606-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6606-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6606-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6606-12 and selecting the quantity you want then