



★ FASTENERS

Military-Fasteners.com

P/N NAS6606-3

Description

length: 0.766", grip: 0.188", thread: 3/8-24, hex head, tension, long thread, cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS66063
Minimum Qty (MOQ):	10
NSN:	5306-01-210-4962
ECCN:	EAR99
National Motor Freight:	093480, Bolts / Nuts Metal Silver Plated



* See page 2 for technical characteristics

P/N NAS6606-3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.563 Inches Minimum And 0.593 Inches Maximum
Fastener Length:	0.741 Inches Minimum And 0.791 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.173 Inches Minimum And 0.203 Inches Maximum
Width Between Flats:	0.553 Inches Minimum And 0.564 Inches Maximum
Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.178 Inches Minimum And 0.198 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Comp 4340 Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Ams 6322 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6606 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6606-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.